

# Veritas R8 Plus

## Control Panel with Remote Keypad

Already renowned for its reliability, the Veritas R8 Plus has been upgraded with a host of new features. Installation and servicing are now even quicker. Operation is easier and more intuitive. Programming has been both simplified and extended. Make the right choice - the Veritas R8 Plus.

### Outstanding Features

- 8 Fully Programmable Zones Plus Tamper
- Upload/Download Compatible
- 8 Channel Communicator Interface with Line Monitor
- EOL or Normally Closed Zone Operation
- 4 Programmable Part Set Suites
- Accepts Up To 6 Remote Keypads (LED or LCD)
- 8 Programmable Access Codes
- 250 Event Log (Time/Date Stamped)
- 1.2mm Steel Enclosure Also Available
- PD6662:2010 Grade 2 Class II



Also Accepts the Veritas Excel LCD Remote Keypad  
Use as an extra keypad or as an engineer's programmer

**Texecom**

# Veritas R8 Plus



## 8 Fully Programmable Zones Plus Tamper

The Veritas R8 Plus features 8 fully programmable zones plus an additional global system tamper. Each zone operates in any of the 8 different zone types ensuring exceptional system flexibility.



## 8 Channel Communicator Interface with Line Monitor

With an on-board 8 channel communicator interface, the Veritas R8 Plus can be used in conjunction with other signalling equipment as part of an ACPO compliant monitored alarm.



## Universal Programming Platform

The Veritas R8 Plus utilises the same intuitive programming platform as the rest of the Veritas Series, ensuring instant product familiarity across the range.

## Specifications

| Veritas R8 Endstation |                              |                             |
|-----------------------|------------------------------|-----------------------------|
| Current Consumption:  | Quiescent current:           | <50mA                       |
|                       | Alarm current:               | <150mA                      |
| Power Supply:         | Mains Supply Voltage Rating: | 230VAC/115VAC (±10%)        |
|                       | Max. Total Current Rating:   | 1ADC at 230VAC/115VAC (±5%) |
|                       | Ripple:                      | <5%                         |
| Dimensions:           | 282mm x 225mm x 80mm         |                             |

| Veritas LED Remote Keypad |                      |                              |
|---------------------------|----------------------|------------------------------|
| Electrical:               | Operating Voltage:   | 13.7Vdc nominal, 10.0Vdc min |
|                           | Current Consumption: | <70mA                        |
| Dimensions:               | 140mm x 105mm x 35mm |                              |

| Veritas LCD Remote Keypad |                      |                              |
|---------------------------|----------------------|------------------------------|
| Electrical:               | Operating Voltage:   | 13.7Vdc nominal, 10.0Vdc min |
|                           | Current Consumption: | <70mA                        |
| Dimensions:               | 146mm x 116mm x 30mm |                              |

## Veritas R8 Plus



## Veritas 8 – G2x Class II

Best selling stand alone control panel. Features 8 fully programmable zones and accepts up to 6 backlit remote keypads.



## Veritas 8 Compact – G1 Class II

Slimline, discreet stand alone control panel. Features 8 fully programmable zones and accepts up to 6 backlit remote keypads.



## Veritas R8 – G2x Veritas R8Plus – G2

Best selling control panels with remote keypad. Features 8 fully programmable zones and accepts up to 6 backlit remote keypads. Veritas R8Plus also includes EOL wiring, communicator interface and accepts Veritas Excel LCD keypads.



## Veritas Excel – G2 Class II

All the features of the Veritas R8 Plus including an LCD keypad for even easier programming and operation.



## European Standards

EMC: Conforms to European Union (EU) Electro-Magnetic Compatibility (EMC) Directive 89/336/EEC (amended by 92/31/EEC and 93/68/EEC).  
 Approved to BS EN 55022 Class B and BS EN 50130-4 : 1996.  
 PD 6662:2010 & EN 50131 Grade 2 Environmental Class II.  
 Texecom products are protected by UK and International patents, trademarks and registered design rights. UK Registered Design Numbers 1573433, 2041830, 2047440, 2055230 & 2089016.  
 Veritas is a trademark of Texecom Limited. ©2012 Texecom Ltd. (LIT-0076-2)



Certificate Number: FM 35285

